



JetWave 2212G-E

Industrial Dual 802.11 ac 2.4G/5G 2T2R MIMO Wireless AP

Dual Band configurable: 802.11 a/b/g/n/ac 2.4G/5G Band
 802.11ac 2T2R MIMO doubles data rate up to 867Mbps per radio
 Remote management by Web GUI, SNMP
 Dual Gigabit Ethernet Port Bridge
 Firewall/DMZ
 Remote management by Web GUI, SNMP
 Dual 24V(12-48V) DC Redundant

Facts

General description

Part number	F00W2212000003
Life cycle status	Mature
Warranty	Up to 5 years

Interface

Ethernet	2x GE RJ-45
WIFI	(JetWave 2212X/S) 1x 2.4G/5G 802.11n, (JerWave 2212G) 1x 2.4G 802.11n or 1x 5G 802.11ac
WIFI antenna socket	2 RP-SMA Female(2T2R MIMO)
DI/DO (dry relay)	0/1
DC power input	Dual DC 24V (12-48V)
PoE mode	Passive PoE

SW/Protocol

DHCP (server, client, Opt 82, port based server)	Yes
Wireless mode	AP, Client, WDS-AP/Client
Routing	support WLAN WAN
NAT/Firewall	Yes
Fast roaming	Yes
802.1x, MAC access control	Yes
Configuration	CLI, Web, Utility, SNMP
Link test tools	Yes
Auto IP report	Yes
Event alarm	DO, E-mail, Syslog, SNMP Trap

Mechanical

Housing/protection (IP)	Aluminum (IP30)
Dimension (HxWxD mm)	140 x 108 x 40
Mounting	Din-Rail, Desktop
Operating temperature	-40~70°C

Certification

Regulatory/approval	CE/FCC/UL62368-1
Compliance standard	E mark
RoHS	Yes

People & Technology. Connected.

We are a people company. Our experienced, skilled and passionate people empower you to meet your challenges through best-in-class, user-friendly solutions. We are a technology company. We help you optimize processes through our software, hardware and services, and through our support. Connecting people and technologies gives you the means to accomplish your goals and ambitions, and gain a competitive edge in today's digitalized world.

Visiting address HQ: Stora Varvsgatan 13a

SE - 211 75 Malmö, SWEDEN

[+46 40 35 86 00](tel:+4640358600) (tel:+46 40 35 86 00)

info@beijerelectronics.com (mailto:info@beijerelectronics.com)